

RSD-60 Rotary Device

Applications

Bits and Cutters
Medical and Dental Parts
Multi-Sided Part Automation
Swiss Screw Parts
Valves and Fittings

Advanced Features and Functions

Horizontal and Vertical Mounting Capability
Intuitive On-Screen Joystick Interface
Seamless Software Integration
Rotate to Position Relative to Current Position
Rotate to Position Relative to a Coordinate System
Rotate to Position Based on Measurements
Automated Rotary Calibration
Non-Linear Calibration Saved to On-Board Memory
Ready to Mount on Micro-Vu Vertex and Excel Systems

Rotary Kit Contents

RSD-60 Rotary Device
Faceplate with Hardened Finish (Ti-Al-N)
Three-Jaw Chuck with Faceplate Adapter
Calibration Artifact and 45° Mirror Assembly
Stage Mounting Bracket
Vertical Mounting Bracket
Cables, Cable Guide, and Routing Brackets
Tools, Mounting Hardware, & Cases

RSD-60 Rotary Device Specifications

External Dimensions	95x150x80 mm
Centerline Height	60 mm
Maximum Speed	120°/second
Resolution	1.3 Arc Seconds
Accuracy	+/- 15 Arc Seconds
On Axis Capacity	1.5 Nm
Chuck Thread	M14 x 1.0
Weight	1.5 kg



Micro-Vu Corporation

7909 Conde Lane Windsor, CA 95492 USA
Phone 707 838 6272 Fax 707 838 3985

www.microvu.com



*502-968-7993 *ISO/IEC 17025 Accredited *www.RegalMetrology.com
Factory authorized Sales, Service, Calibration, and Training
Serving Indiana, Kentucky, Tennessee, Alabama, Mississippi, and Illinois